

XM 4CH 5MPN 6IN1 DVR



Key Features



Support intelligent analysis: Human detection, face detection, Vehicle shape detection VIOT,coaxial audio;

Support H.265 encoding, ultra-low bitrates, compatible with H.264 surroundings;

Support VGA, HDMI full HD output simultaneously;

Support ONVIF; access third party;

Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

Support web, VMS, center platform management software MYEYE, provide SDK development;

Support various mobile monitoring (iPhone, Android);

Remote Access, With DNS (ARSP),easy to monitor remotely

Support UTC, control signal& video stream transmit through one single coaxial

Support XVI/AHD/TVI/CVI/CVBS/IP six signals;

Network

Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.)

Structure

Temperature:0 - 55 , Humidity:10% - 90%RH , Atm:86kpa - 106kp

Wide voltage range of 12V±10%

Specifications

Model	HX-XMD3004L5MN
Technical parameters	
Main processor	NT98331
Preview	1/4/8/9
Codec	H.265
Monitor quality	VGA(1080P at most);HD II(1080P at most)
Preview ability	4*5M-N@20fps (6 in 1) /4*4M-N@30fps (6 in 1) /4*1080P (6 in 1) default:5M-N
Encode ability	4*5M-N@20fps (6 in 1) /4*4M-N@28fps (6 in 1) /4*1080P@25fps (6 in 1) default:5M-N
Decode ability	2*5M-N@20fps (6 in 1) /2*4M-N@28fps (6 in 1) /2*1080P@25fps (6 in 1) default:5M-N
Multi-mode input	Analog : 4*5M-N hybrid : 4*5M-N (analog) +2*1080P (network) network : 16*1080P;8*5M
Digital to analog conversio	Unsupport
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio compression	G.711A
Intercom	support
Recording mode	Manual>Alarm>Dynamic Detection>Timing
Local playback	2ch(analog input mode)
Search mode	Search by time, calendar, event, channel
Record storage	HDD、 Network
Backup mode	Network backup, USB hard disk, USB burner, SATA burner
Video output	4ch BNC
Video output	1ch VGA, 1ch HDMI, 1CH BNC
Loop Vout	N/A
Audio I/O	1/1
Alarm I/O	0/0
Network interface	RJ45 10M/100M self-adaption
PTZ control	Support kinds of PTZ protocols
USB	2* USB 2.0 ports
Network protocol	support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.
Upgrade	Support USB mobile hard disk, U disk Support USB DVD burner
Wireless	3G, WIFI (extendvia USB)
ONVIF	Support
Surge Protection	Surge Protection 2KV
Remote access	
Browser	Supports multiple web browsers
Client	Support VMS
APP	Support for iPhone, Android MYEYE
Storage	
HDD number	1*SATA ports (Max 6TB/per)
Others	
Power supply	DC12V /2A
Work environment	Temperature:0 - 55 , Humidity:10% - 90%RH , Atm:86kpa - 106kp



Dimensions

